

### Specifications

Models	GL-4		GL-8		GL-10		GL-12	
Measurements	US	Metric	US	Metric	US	Metric	US	Metric
<b>A</b> Height - stowed <sup>1,2,3</sup>	5 ft 7.5 in	1.72 m	5 ft 7.5 in	1.72 m	6 ft 6.5 in	2.00 m	7 ft 7 in	2.31 m
maximum forks down	4 ft 1.5 in	1.26 m	8 ft 3 in	2.51 m	9 ft 10.5 in	3.01 m	12 ft	3.66 m
maximum forks up	5 ft 11 in	1.80 m	10 ft .5 in	3.06 m	11 ft 8 in	3.56 m	13 ft 9.5 in	4.20 m
minimum forks down	3.5 in	.09 m	3.5 in	.09 m	2 in	.05 m	2 in	.05 m

#### Standard Base

<b>B</b> Length - stowed	1 ft	.30 m	1 ft	.30 m	————	————	————	————
operating	2 ft 10.75 in	.88 m	2 ft 10.75 in	.88 m	————	————	————	————
<b>C</b> Width: outside	2 ft .75 in	.63 m	2 ft .75 in	.63 m	————	————	————	————
Weight - standard caster options	113 lbs	51 kg	132 lbs	60 kg	————	————	————	————
pneumatic caster options	117 lbs	53 kg	136 lbs	62 kg	————	————	————	————

#### Straddle Base

Length - stowed	1 ft 7.25 in	.49 m	1 ft 7.25 in	.49 m	1 ft 7.25 in	.49 m	1 ft 7.25 in	.49 m
operating	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m
Width - stowed <sup>4</sup>	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m
maximum <sup>4</sup>	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m
maximum inside	3 ft	.91 m	3 ft	.91 m	3 ft	.91 m	3 ft	.91 m
Weight - standard caster options	126 lbs	57 kg	145 lbs	66 kg	149 lbs	68 kg	154 lbs	70 kg
pneumatic caster options	130 lbs	59 kg	149 lbs	68 kg	153 lbs	69 kg	158 lbs	72 kg
4-point caster option	139 lbs	63 kg	158 lbs	72 kg	162 lbs	73 kg	167 lbs	76 kg

#### Counterweight Base

Length - operating	2 ft 4.5 in	.72 m	2 ft 4.5 in	.72 m	2 ft 4.5 in	.72 m	————	————
Width - stowed <sup>4</sup>	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	2 ft 4.75 in	.73 m	————	————
maximum <sup>4</sup>	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	————	————
maximum inside	3 ft	.91 m	3 ft	.91 m	3 ft	.91 m	————	————
Weight - standard caster options	392 lbs	178 kg	411 lbs	186 kg	433 lbs	196 kg	————	————

### Productivity

Load height minimum	3.5 in	.09 m	3.5 in	.09 m	3.5 in	.09 m	3.5 in	.09 m
Ground clearance - center <sup>1,2,3</sup>	.75 in	.02 m	.75 in	.02 m	.75 in	.02 m	.75 in	.02 m
Average cranks - standard winch	11.5/ft	38/m	11.5/ft	38/m	11.5/ft	38/m	11.5/ft	38/m
Fork length	1 ft 10.5 in	.57 m	1 ft 10.5 in	.57 m	1 ft 10.5 in	.57 m	1 ft 10.5 in	.57 m
Fork width	1 ft 8.5 in	.52 m	1 ft 8.5 in	.52 m	1 ft 8.5 in	.52 m	1 ft 8.5 in	.52 m
Load platform length	1 ft 11 in	.58 m	1 ft 11 in	.58 m	1 ft 11 in	.58 m	1 ft 11 in	.58 m
Load platform width	1 ft 10 in	.56 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m
Load capacity at								
12 in (30 cm) load center	500 lbs	227 kg	400 lbs	181 kg	350 lbs	159 kg	350 lbs	159 kg
Boom length	20.19 in	51 cm	20.19 in	51 cm	20.19 in	51 cm	20.19 in	51 cm
Boom attachment points	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm

### Power


Power source                      reversible standard winch

<sup>1</sup> The 10 in pneumatic rear wheel option will add 1 in (2.5 cm) to these specifications.

<sup>2</sup> The counterweight base will add 1 in (2.5 cm) to these specifications.

<sup>3</sup> The 4-point caster option B will add 1 in (2.5 cm) to these specifications.

<sup>4</sup> Outside dimensions.



### Features

#### Standard Features

##### Measurements

###### GL™-4

- 5 ft 11 in (1.80 m) maximum lifting height
- Up to 500 lbs (227 kg) load capacity

###### GL-8

- 10 ft .5 in (3.06 m) maximum lifting height
- Up to 400 lbs (181 kg) load capacity

###### GL-10

- 11 ft 8 in (3.56 m) maximum lifting height
- Up to 350 lbs (159 kg) load capacity

###### GL-12

- 13 ft 9.5 in (4.20 m) maximum lifting height
- Up to 350 lbs (159 kg) load capacity

##### Productivity

- Portable and compact design
- Lightweight durable aluminum construction
- Single door access
- Durable standard steel forks
- 8 in (20 cm) non-marking rear wheels and 2 in (5 cm) dual wheel front swivel casters (standard and straddle base only)
- 5 in (12 cm) rear swivel casters with side brakes and 4 in (10 cm) fixed front wheels (counterweight base only)
- Loads easily into a pickup truck for transporting
- Hold-down mechanism secures carriage during transport

##### Power

- Standard winch
- Reversible winch handle for easy storage

#### Options & Accessories

##### Productivity & Fork Options

- Standard forks
- Load platform
- Aluminum ladder (standard and straddle base only)
- Foot-release brake (standard and straddle base only)

##### Power

- Winch operates while ladder is in use or stowed
- Caster option kit required for use with Straddle bases

##### Base Options

- Standard base (GL-4, -8 only)
- Straddle base (all units)
- Counterweight base (GL-4, -8, -10 only)

##### Wheel/Caster Options

###### Straddle and standard base

- 8 in (20 cm) non-marking rear wheels
- Pneumatic rear tire option
- 2 in (5 cm) dual wheel front swivel casters

###### Counterweight base

- 5 in (12 cm) rear swivel casters with side brakes
- 4 in (10 cm) fixed front wheels

###### Straddle base

- 4 point caster option



#### Genie United States

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington 98073-9730  
Telephone +1 (425) 881-1800  
Toll Free in USA/Canada +1 (800)-536-1800  
Fax +1 (425) 883-3475

#### Genie Europe

The Maltings  
Wharf Road  
Grantham NG31 6BH  
UK  
Telephone +44 (0)1476 584333  
Fax +44 (0)1476 584334  
Email: AWP-InfoEurope@terex.com

#### Distributed By:

Effective Date: February, 2012. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2012 Terex Corporation.